


Hobbies

WEEKLY

Make this
CATAMARAN

ALSO FREE
DESIGNS FOR
**DOLL'S
KITCHEN
MODELS**




August 6th. 1938

2^D


Vol. 86. No. 2233

**THE FRETWORKER'S AND
HOME CRAFTSMAN'S JOURNAL**



FREE with HOBBIES 1939 HANDBOOK

Take our word for it. Hobbies 1939 Handbook is the best we have published. It's the biggest sixpennyworth the handyman can get. 284 pages.....500 things to makea mine of information. And if you like value for money, just look at this! With every copy we give you absolutely FREE a large design sheet (value 1/6) for making a handsome model Big Ben 8-day Clock which stands 3ft. high when completed. Here is something you will treasure for the rest of your life. Then there is a design (yours for the asking) for building a fine working model Paddle Steamer 22ins. long, which works from an ordinary flashlamp battery. Hobbies 1939 Handbook is the book without a substitute. Get your copy NOW! It is too good to miss.




284 Pages

•
500 Things
to Make


•
A Marvel
of Value

6^d.

6d. Post free, from
Hobbies Limited,
Dereham




Get Yours NOW



Hobbies

WEEKLY



August 6th. 1938

Vol. 86. No. 2233

I HAVE received a number of requests from readers who have visited the Empire Exhibition at Glasgow, if we cannot have some souvenir in wood to make. So I have had a small Wall Plaque designed and hope to be able to publish it within a week or two. It will serve as a pleasing reminder of this mammoth Exhibition, the size of which has to be seen to be believed.

WHEN you remember nearly 80,000 people stroll round its grounds and pavilions in comfort daily, you can realize something of its magnitude. But of that, more later, when the design is published. In the meantime have your H.W. delivered regularly to make sure not to miss a single copy.

DURING the summer months I have been having fewer articles on Electrical matters, and increasing our outdoor pastimes. Soon, however, there will be a return to the regular electrical articles, and in this respect I shall be glad to hear of any particular instrument, or apparatus, or experiment you would like introduced. I have warned the Electrical Expert to be getting along with some bright ideas and I hope to give you some real novelties, as well as practical instruction. At the same time I want suggestions from you as to what you would like incorporated in the Electrical series.

AS an extra incentive for you to give some thought to the matter, I shall send a small prize to anyone who makes a suggestion which I can carry out later on. Come on, then, put on your thinking caps or let me know what electrical problems you have. A short note is sufficient, providing you make it clear what you want.

DO you think it was ignorance or a touch of wit that I received a note the other day addressed to the "Territorial" Dept.? Really, of course, it was intended for the "Editorial" Dept., but I

have an inkling that somebody was for pulling my leg! I wonder?

IT was very nice to receive a cutting from J. A. Gresty of Market Drayton, containing much interesting detail about the old sailing ship the "Cutty Sark". We have a special interest, of course, because our model has been made up by keen readers all over the world. The famous tea clipper is now resting on the Thames at Greenwich, after an adventurous and oft-times stormy life.

IT is said of her that in spite of regular journeys to China and Australia in all weathers, she never sprang a leak. It sounds quaint, but in 1889 she had a race against a steamer and reached Sydney 4 hours ahead. Her extra speed was, of course, a great asset in those days, because the first home from China with the new season's tea could always make an extra profit. A good average, then from England to China, was about 100 days—over three months. Compare that with the speed of today's mail steamers—to say nothing of the improved comfort!

"ALLOW me to add that I have had the great pleasure of using a Hobbies Handframe, etc. for the past 25 years. That is, of course, when I have had the precious time to give to the hobby. I am sorry to say I cannot find sufficient time, owing to my work, to spend on the world's greatest Hobby as I would wish." That's what T.R.B. of Eastbourne thinks, and says, about it and I am sure there must be thousands who agree with him. What?

CONTENTS

Fun and Puzzle Page	434
Doll's Kitchen Set	435
Hobbies League Correspondence Club	436
Making a Catamaran	437
Photograph Competition Winners	439
Scout Notes	440
Electrical Pole-Finding Devices	441
Doll's Chair and Table Patterns	444
Garden Frame and Tool Shed	447
Model Galleon Stands	449
Gardening in August	450
Hiking at Night	451
Preparing Wood Surface	452
Sport Silhouettes in Wood	453
French Celebrities on Stamps	455

Correspondence should be addressed to: The Editor, Hobbies Weekly, Dereham, Norfolk, and a stamp enclosed with the Reply Coupon from Cover iii if a reply is required. Particulars of Subscription rates, Publishing, Advertising, etc., are on cover iii.

THIS week sees the publication of the new Hobbies Handbook for 1939, and an interesting announcement regarding it is given on the facing page. The book is quite a new edition with interesting articles on things to make as well as two large free design charts and a Calendar cut-out picture in colour.

The Editor



FUN AND PUZZLE



Why would a sparrow be angry if you called him a pheasant?
You would be making game of him.

Why did the hen run?
Because it saw the fox trot.

What game is played by a ship?
Pitch and toss.

Why is a weary man like a motor wheel?
Because he is tired (tyred).

WHY NOT?

A man went away and asked his secretary at the office to forward business correspondence. She wrote saying he had the key of the letter box. He wrote enclosing the key but still received no correspondence. It's a tricky little problem you should be able to solve. If not turn to column 3 for the solution.

A FIXTURE

Dolly was ailing, so mother had taken her to see the doctor.

"Put your tongue out, my dear," said he.


A minute pink tip just showed itself.

"That won't do," said the doctor heartily. "Put it right out."

"I can't," replied Dolly. "It's— it's joined at the back."

SEE THESE STEPS?

Can you believe your eyes? This series of steps is not really that at all, but is made up of one continuous line from top to bottom. Now look more carefully and you will see what we mean.



Why is an egg like a drum?
Because both can be beaten.

Can the sardine box?
No, but the tomato can.

When is a man a reptile?
When he's a bookworm.

What is it impossible to buy?
A sheet for the bed of the river.

MORE HOWLERS

Septuagenarian—a person born in September.

Temperament—one who promises never to drink again.

As the arrow struck his eye, King Harold shouted "A hearse, a hearse, my Kingdom for a hearse."

Extradition—a newspaper term for special paper.

Cataclysm—what you have to learn in Sunday School.

An indenture is a set of false teeth.

Plato is the name of the dog in Micky Mouse films.

NO NUMBER PLATE.

"Hi! What's the idea—you've got no number plate?"

"Oh, that's quite all right. I can remember it."

Solution to Last Week's CRICKET X-WORD

B	A	T		W	I	L	L	O	W	
O	V	E	R		N		R	U	I	N
W	A	G		B		P	I	T	C	H
L		S	C	O	R	E			K	
E	H		C	U		A	S	H	E	S
R	O	B		N	O		U	T	I	
	B	R	A	D	M	A	N		X	
P	B		B	A	I	L		A	M	
A	S	S	O	R	T		S	T	A	B
D		I	V			H	A	T		Y
S	I	D	E		C	R	E	A	S	E

When is a theatrical manager like an astronomer?

When he discovers a new star.

Why are sentries like night and day?

Because the one comes as the other comes.


NATURAL.

Glasgow is laughing at this topical story. Bellahouston is, of course, the home of the Empire Exhibition, and Maryhill are two of its suburbs.

At the station booking office two women and a man were standing. The first woman said "Maryhill single." The second woman "Bellahouston single." The man said "Pat Murphy, married."

A MATCH TRICK.

Take twenty-four matches and form them into a square of nine smaller squares so that there are three rows of three. You are required to take away eight matches so that two squares only remain. The puzzle is tricky unless you know the answer. The drawings show you both. Try it on a friend.



A TONGUE TWISTER

Try and say this quickly: I guarantee this can-opener can open any can a can-opener can open, and if this can-opener can't open any can a can-opener can open, I give you this can-opener free.

STILL RUNNING

The teacher had taught his class that the Equator was an imaginary line running round the middle of the earth.

He was surprised to hear a few days later that one of the "dangers" of the tropics was the Equator.

"What makes you say that, Willie?" he asked.

"You said it was a menagerie lion, an' if it's running all round the middle of the earth it must be dangerous, 'cos it's not caged up."

What is always behind time?

The back of a clock.

Why is a fish like a shopkeeper?

Because it has scales.

What will make pies inquisitive?

S will make spies of them.

When is a fowl's neck like a bell?

When it's (or) rung for dinner.

SOLUTION.

Here is the reason for the non-arrival of the correspondence.

The letter was naturally put by the postman into the locked letter box. It could have been avoided by sending the key in a registered letter, which is delivered to some person in order that a signature can be obtained of its receipt.

Patterns are provided for this DOLL'S KITCHEN SET

THE patterns in the centre pages of this week's issue provide the making of another of those interesting units in the series of doll's house kitchen furniture which we have published recently.

Here we have a kitchen table and one chair, but, of course, we can add to the chairs as much as we like by duplicating the pattern provided.

All these models are to scale in proportion to each other so that gradually we shall have built up a complete model kitchen and finally provided for it a stand and background to make the whole assembly complete. All the parts are straightforward to cut and very little work is required.

Suitable Finish

When finished the models are painted or stained according to the full size articles. In the case of the table this can be left with the wood in its natural state or the legs and rails stained dark or just varnished.

The chair, too, can be stained and varnished, but the table top itself should be left in its natural state, because later on no doubt the happy owner will want to cut table cloths to cover it or to fit up an American cloth as a permanent addition.

If you get the parcel of wood mentioned here you will find all the boards of the correct size and thickness for the various parts required, and this saves a good deal of cutting out.

Indeed, as several of the pieces are plain rectangles two of the sides of the patterns can be pasted down in line with the edge of the wood and so save the cutting. In addition it ensures a perfectly straight edge.


Complete Patterns

The patterns are shown full size with the exception of the floor, and this has had to be broken to get it on the page. All you need do, however, is mark off a rectangle on a piece of $\frac{1}{8}$ in. wood $4\frac{1}{8}$ ins. long and $2\frac{7}{8}$ ins. wide.

Of course, the same applies to the other rectangular patterns where it is a simple matter to transfer their size direct to the wood without actually pasting the pattern on to it. Lay the paper on the wood carefully, then prick a small hole in each corner of the part. Take the paper away and link the holes up with a ruler and you have the size and shape required.

MATERIAL SUPPLIED

Parcel of wood.—For making this design we supply a parcel of selected Beech including two (No. 80) Knobs for 1/6 or sent post free 2/.



Full size patterns on pages 444 and 445

The construction should be straightforward, but it is best to notice the various parts which join each other. These are lettered on the patterns, but this lettering will not be available after the pieces have been cleaned up.

Lettered Parts

A good plan, however, is to draw the letter on the back of the wood lightly in pencil so you still have a reference when the paper is cleaned off.

On the other hand, after a little study of the patterns and the drawing of the finished article, there should not be much need for letters at all. Take out the parts and test them together after cleaning up, as you go along. You may decide to cut the table or the chair first—it is immaterial which.

The Table

The table is straightforward with a plain top to which are added four rails, four legs and the drawers. First get the legs out in $\frac{3}{8}$ in. wood. These taper from a dotted line shown across the pattern, and we must also taper down the other two sides to correspond with it.

Now get out the front and back rails. They are shown in one pattern but in the case of the front the table drawer is cut from the same piece. For the back you have a plain outline $4\frac{1}{8}$ ins. by $1\frac{3}{8}$ ins.

The front is a similar sized piece, but the pattern shown should be pasted down so you can cut out a centre panel. Put a tiny drill hole in one corner, and use a saw to go round between the two lines shown. This part which comes out is the drawer front to be made up later.

To complete the table, get out the two end rails and put all four of them between the legs. Notice that each pair is exactly the same size or it will throw out the legs of the framework.

The legs are set inwards about $\frac{1}{4}$ in. from the edge of the top then the four rails glued between them. Note, as shown by the dotted lines on the table top pattern, that these rails are not set in line with the actual legs but slightly back from their front face.


Get these rails glued firmly between the legs and also to the underside of the table top.

One of the points to be particularly careful of is to see the distance between the rails is the same in order to allow the drawer to run in and out easily.

The Drawer

The construction of the drawer itself is shown in the detail herewith. Get out the floor, back, two ends and the inner front. The four side pieces forming the upright frame are glued on to the floor then the front cut from the rail is glued on.

This covers the join of the front and floor and fills up the opening in the table itself. In making



up the drawer, see it will pass through the opening in the front rail and rub the edges down lightly with glasspaper to make this more comfortable.

The runners on which the drawer slides are made up by two pieces of wood. One is a guide and one is a runner and they are glued together as shown in the drawing. Each is a similar piece of wood, but one is cut from $\frac{3}{4}$ in. and one from $\frac{1}{4}$ in. They are glued inside the rails of the table just far enough apart to allow the drawer to slide along the floor piece.

The front of the drawer is fitted with two of the tiny knobs (No. 80) which are sunk a little way into the hole made with a drill point or bradawl and there glued in place.

The Chair

The chair is built on the two side frames, the seat fitting into the little slot joint at A, and the other cross rails being glued between. Notice which are plain cross rails and which are shaped as well as their position between the sides.

Here again all rails must be exactly the same length or you will not get a good fit for the completed article. The two flat ones B form the supports back and front under the seat. They are not put flush with the front edge of the sides, but set back nearly $\frac{1}{4}$ in.

The cross rail C is the flat one fitting between the bottom rail of the sides. These lettered D and E are the fancy rails of the back. The top edge of E should be rounded off to make it more shapely and realistic, and is then glued between the sides a little way inwards from the top and front. The rail D comes $\frac{3}{4}$ in. below that.

Constructional Methods

The best method of construction is to lay one of the sides flat on the bench then glue the rails upright on it in their proper position. Then get the other side and having glued the edge of the rails put it in place.

Let the whole framework set, then glue the edges where the seat will come and slide that piece into place into the joints at A. You must be careful to test the distance between the sides and the slot joints in the chair seat.

If these are not the same you will either force the sides apart or break off the small projecting pieces which should fit in place.

After construction and the glue is all set, give the whole thing a final rubbing with glasspaper then complete by means of stain and varnish. Take care if you are varnishing the front of the table, not to apply it to the drawer so it sticks.

HOBBIES LEAGUE CORRESPONDENCE CLUB

These Members of Hobbies League would like to get in touch with other readers and so form pen friendships which will undoubtedly prove interesting to all. In this way, one has a wide circle of friends and increased knowledge in people and places, not only in one's own country, but all over the world. Members should write direct to the addresses given, stating their full address and age, adding any hobbies in which they are interested. Hundreds of members have already taken advantage of this Correspondence Club in this way and others who wish to do so should notify the Registrar with the necessary particulars.

NAME	ADDRESS	WANTS FRIENDS	INTERESTS, Etc.
Master E. Bowman.	Bleach Green, Witton Gilbert, Co. Durham.	Brit. Colonies.	Stamps, Fretwork, Woodwork and Engineering.
Mohamed Kamel Elmogy.	8 Luvy St., Qobeh Gardens, Cairo, Egypt.	England.	Anything.
V. Ruthensamy.	c/o 162 Forrest Rd., Overport, Durban, S. Africa.	England, Toronto, Mozambique, Egypt.	Fretwork, Cig. Cards, Stamps and Electricity.
Maurice Tan.	20 Lorong 28, Geylang, Singapore, S.S.	Anywhere.	Stamps, Snaps, Fretwork, Post Cards and Air Mail Envelopes.
S. A. Uchendu.	Government School, Ajalli, Awka District, Onitsha Prov., Nigeria, W. Africa.	England.	Anything.
PD. M. Epo.	St. Charles Training College, Onitsha Town, S. Nigeria.	Anywhere.	Stamps.
V. I. O. Ijeh.	c/o John O. Ijeh, Contractor, Umu-Ahia, S. Nigeria.	Anywhere.	Anything.
C. I. C. Nwoke.	c/o P. N. Nwoke, Posts & Tells., Onitsha, Nigeria.	Anywhere.	Anything.

You can get great fun from

A CATAMARAN

THE catamaran is a type of vessel having much to recommend it. It is comparatively easy to construct and is as safe as any vessel can be. Of course, it is not a speed boat, but is excellent for navigating shallow, weed infested waters and for river sport generally.

A side view is given in Fig. 1, which, with the end view in Fig. 2 will give a good idea of the construction. Make the pontoons first. These consist of two boards, nailed to vertical divisions A-B.

Curve the boards to a point at the fore ends; at the rear ends they are curved to leave a flat, 2ins. wide, to which the rudders will be hung. Posts, C-D are nailed to the ends.

The Pontoons

They are cut from 2ins. by 4ins. stuff and have their outside edges planed to the curve of the sides. Get all the outside edges level, trimming them with a plane if necessary, so that the sides of the pontoons will bed down satisfactorily and not leave gaps.

At E, glue a 2in. sq. block of wood in the centre of the top board underneath, to provide a foundation for the screw hook holding the mast stays.

The centre of this should be marked on the top of the board by a cross, as a guide to fixing the hook. Also draw pencil lines across directly above the centre of the division pieces as a guide to exactly where they are. This will be helpful when fixing the cross bars afterwards.

Use Good Plywood

Plywood, of a quality that will bend to the curve, should be chosen and should be cut in strips with the grain running across to facilitate the bending. Coat the outside edges of the boards, division pieces and posts with thick paint, lay the plywood over and nail closely in contact.

Where joins in the sides are necessary, arrange for these to come over the division pieces. At the fore ends butt the meeting edges of the plywood neatly together and at the rear ends, trim off level with the flats of posts D. Fig. 3 shows the pontoon cut away to give construction.

The sides of the pontoons are to be covered with some material, calico will do, as the water will play havoc with the plywood otherwise. Cut strips for the

purpose long enough to reach the full length of each side and with an inch to spare, top and bottom, for bending over.

The Covering

Apply to the sides a coat of thick lead paint, lay the calico over and rub well down into contact. Make a neat job and avoid creases. Where the material meets at the ends, fold together and copper tack down.

The spare inch top and bottom is best glued over to hold down securely. Snip the curved parts to avoid creases.

The cross bars, F, G, are now cut to length and screwed to the pontoons. Two screws will be enough each side and preliminary holes should be bored for them.


Ordinary wood screws are not used for this job, but 4in. coach screws, as in Fig. 7, driven in with a spanner. These screws will be driven through the bars into division A, B, the pencil lines previously drawn across being taken as guides for boring the holes in the right place.

Planed slips of wood, $\frac{3}{8}$ in. by 1in., are nailed along against the edges of the top and bottom to cover the turned down edges of the calico, as in Fig. 4. Wider slips must be used for the curved ends, the outer edges being sawn to the curve to correspond.

Before fixing these, coat the undersides of the slips with thick paint to make the joints watertight.

The rudders are cut from $\frac{1}{2}$ in. thick wood, preferably a hardwood such as oak or elm, with the grain running across the narrow part. These are hinged to the rear of the pontoons, as in Fig. 5, with 1oin. T hinges. Fix so that the back edges are $\frac{1}{4}$ in. clear of the pontoons, and round the edge so that they swing freely.

In the centres of the tops,



The completed craft
afloat

drive in a stout screw eye. The rudders are linked together by a bar of $\frac{1}{2}$ in. by $\frac{3}{8}$ in. iron. Drill two holes in the iron link the correct distance apart and drive the screw eyes through these into the rudders.

Steering Gear

Lines for steering are tied to the screw eyes, and crossed so that the line attached to the left rudder comes to the right side of the boat, and vice-versa. The ends of these lines can be passed through screw eyes or small pulleys, fixed to the sides of the platform at convenient spots.

Now give the whole pontoons two coats of best lead paint all over, enamel the iron links, and well grease the hinge pins.

The platform consists of sides and ends, joined to a stout floor of T. and G. boards with screws. Note the fore ends of the sides are curved and taper from 6 ins. high at the front to 4 ins. at the rear. Fig. 6 shows part of the platform and how the mast is supported.

These supports are cut from 1 in. thick board, are 4 ins. by 12 ins. and shaped as shown. The top one is screwed to the front of the platform, the bottom one to the flooring. Holes are bored of a size to admit the mast freely but without wobble.

A low seat is provided. This is a 9 in. wide board, of at least 1 in. thickness. A back is recommended for comfort and is a 4 in. wide rail, screwed to side supports near each end. Fit the supports at a slight backward angle, and as a strong joint to the seat is very necessary, groove in $\frac{1}{2}$ in. deep and screw from beneath, as in Fig. 8.

The ends of the seat fit between strips of wood each side, as shown in dotted lines, so that it can be shifted along to the most convenient position. Fix the platform to the cross bars with bolts and nuts.

The Mast and Boom

The mast is a length either of straight grained spruce or bamboo, about 2 ins. diam., tapering to 1½ ins. at the top.

The boom is similar, or can be a trifle less, say 1½ ins. diam. To each end of the latter fit a screw eye. To hook the boom to the mast, drive in a screw hook, as seen in Fig. 1.

At the top of the mast, fix a hook on which a pulley block can be hung for raising the sail. A little below this fix a hook each side for the mast stays to be attached to. Similar hooks are screwed in the pontoon, as shown in Fig. 1. This illustration also shows how the mast stays (strong lines), are fitted.




Fig. 1—A side view with helpful dimensions of craft and sail




Fig. 2—An end view, showing pontoons




Fig. 3—Cutaway view of pontoon showing construction




Fig. 4—Fitting the calico




Fig. 5—The pontoon rudder




Fig. 6—The mast and pontoon detail



Fig. 7—Screw fixing




Fig. 8—Seat supports

Calico will do for the sail, a pattern of which should be cut out of paper. No difficult job this if done the proper way. Paste a few sheets of paper together to form a large enough sheet, and mark off line A, B on one edge.

At the correct distance from b, mark off point c, and from there and at right angles to a—b draw c-d. Connect points a-d and b-d, and cut out.

Lay the calico flat and free from creases, place the pattern over with the edge a-d against the selvedge edge of the calico, pin to it, and cut out the material, allowing 1in. all round for hemming.

In each angle insert a small piece of material to strengthen the corners, and hem all round, inserting a length of cord in the hems along a-b and b-d. At intervals of gins. fix brass eyelets for lashing to the boom and mast.

Two widths of the material will be required to make up the full width of the sail, and the join should run parallel with edge a-d. The catamaran is now completed, except for minor details.

The platform, etc., should receive two coats of

paint or varnish, also varnish the mast and boom. A cleat should be fixed near the bottom of the mast to which the line, used for raising the sail in position, can be secured.

A similar cleat should be fixed to the side of the platform to hold the line which controls the movement of the boom.

Cutting List

	No.	Length.	Width.	Thickness.
Pontoon boards	4	10ft. 0ins.	11ins.	1in.
Division pieces	4	0ft. 10ins.	11ins.	1½ins.
Posts	4	0ft. 10ins.	4ins.	2ins.
Cross bars	2	5ft. 4ins.	2ins.	2ins.
Platform sides	2	6ft. 1in.	6ins.	1in.
Ends	1	3ft. 4ins.	6ins.	1in.
Ends	1	3ft. 4ins.	4ins.	1in.
Rudders	2	1ft. 0ins.	15ins.	½in.
Seat	1	3ft. 4ins.	9ins.	1in.
Seat ends	2	1ft. 0ins.	4ins.	1in.
Back rest	1	3ft. 4ins.	4ins.	1in.
2½ sheets, 5ft. by 4ft. of ½in. or 3/16in. plywood for pontoon sides.				
60ft. 1in. T and G floorboarding for platform.				
30ft. ½in. by 1in. strip and 60ft. ½in. by 3in. strip for covering pontoon edges.				
12ft. ½in. by 1in. strip for seat guides.				

PHOTO COMPETITION WINNERS

THE number of entries for this month is a little disappointing, seeing that we are offering prizes for a variety of subjects of a very simple nature—namely Sports, Landscapes and Gardens. The quality of the work, too, is not as good as we have had in the past.

Some of the entries really do not quite answer to any of the subjects and we should like all competitors to watch this point because they might be entering a very fine photograph but be spoiling their chance of a prize by sending it in

when there is not a class for that subject. For instance, a study of a dog cannot compete in a landscape class, and such a print should be kept for competing in a class for animals.

The Open Section

In the Senior Class the first prize goes to G. E. Hewitt of Gainsboro', for "Young Beekeepers have confidence." We are stretching a point here because it could be a garden scene or even a sports subject. Photographically, it is very good, as regards exposure, developing and printing.

The second prize is awarded to W. Evenden, of Ashford, Kent, for "Springtime." A pleasing picture, which would have been much better if horizontal instead of upright.

D. Waddingham, of St. Albans, made a very good attempt at a difficult subject, which would have been greatly improved if the amount of foreground could have been reduced. It rather overpowers the view.

Junior Section

In the Junior Section the first prize must go to Peter Bloomfield, Reading, for a snap of Goring-on-Thames. This is a nice little picture, but it would have been better without the tree on the extreme right where all detail is lost.

Second prize is taken by James Grayshan, of Bradford, for the "Drawbridge and Moat at Wells." Here again the trees overhead are lacking in detail, largely because they are under exposed.

Prizes have been sent to the winners, and we hope all those not fortunate now will try again in the remaining competitions. There is still an opportunity.



The Prize Winning "Snap" in the Open Section

Lots of interesting things in these SCOUT NOTES

What to Look For

ALTHOUGH a happy camping month, August is tinged with sadness as far as nature is concerned, for it tells us of the first approach of Autumn. Our friend the Robin will be heard telling you in song of this imminent change of season.

However, it is a very pleasant month and troop or patrol funds may be augmented by fruit picking or helping with the harvest. Either of these occupations proves a pleasant means of doing a good turn to the farmer who loans you his field. Do not forget to look for Harvest Mice nests in the corn.

The stripping of the fields of their crops will drive many of the animals (stoats, weasels, game, etc.) who spend the summer therein back to the woods and forests. To huntsmen August means the starting of the cubbing season.

Duck and Grouse shooting begins this month, and, for those who do not mind going out early in the morning, mushrooms may be gathered. A good breakfast dish this for camp, but make sure they are mushrooms before you eat them.

The Camping Month

ONCE more the camping month of the year has come round again and good camping is my sincere wish to you all. There are so many campers of various sorts about now that it behoves all Scouts to put on their best behaviour and not abuse the privileges allowed them in order that the many restrictions on camping which are found to be necessary may not be applied to the Scout movement.

Remember that how you conduct your camp this year may mean everything to the Scouts ten years hence. For bad camping will mean more restrictions and so future generations will suffer for your sins of omission.

There is a very interesting little pamphlet issued by H.Q. on "Camping Rules" and I strongly advise all who have time to send for one or ask your Scoutmaster to lend you his copy. Study this and carry out the suggestions therein and you need have no fear of visiting Commissioners.

Camping Hints

ABIRD cage covered with muslin and hung under a tree makes an ideal cool safe for butter, etc., while at camp. The muslin keeps out flies and other insects and if hung in the shade keeps things fresh and cool. Hang out of reach of animals.

A suitable tree and a few boards and lashing and a fine lookout can be made. If a rope ladder is used also it can be drawn up and the look-out made inaccessible.

A layer of brown paper between two blankets or under a bed greatly increases the warmth of the sleeper.

Great difficulty is often experienced in loosening the joints of lightweight and other tent poles. Polish the joints with blacklead and this difficulty is soon overcome.

Fat for frying should be thoroughly hot before using. When the top of the fat begins to smoke a little—that is the time to put your food into it. Insufficiently hot fat causes the food cooked in it to taste of grease.

Smile and Win

EVERY Scout should obey the eighth Scout Law and as we are now starting our regular monthly competitions again, here is one which will give us an opportunity of judging whether you are a really good eighth law scout or not.

Send in on a postcard what you consider the best joke you have heard lately and a handsome prize will be forwarded for the best effort. Consolation prizes will be awarded as well.

Address your entries to "Scout Competition" Hobbies Weekly, Dereham, Norfolk, and send them in by August 13th.

Some of those jokes heard round the camp fire must be worthy of reproduction and we will publish the best one submitted in our October issue.

I don't want you just to copy one out of another book because that wouldn't be fair. There must be lots of tales you will actually hear—well, write them out and send on to me.

Air Raid Precautions

IN view of the National interest in A.R.P. (the abbreviation for Air Raid Precautions) I intend giving a few notes on this subject month by month. Scout readers of this magazine may thus be ready in case of an emergency to offer their services in the various capacities set out for Youth Organisations.

Many older members of the Scouts will remember with gratitude the services rendered by Scouts during the last war and although we hope and believe that such a catastrophe will not happen again it will be in accordance with our Scout Motto in being prepared to help should the necessity arise.

We will start off with a very brief survey of the various gases likely to be used in warfare. Gas in the A.R.P. sense is "Any chemical substance solid, liquid or gas used in warfare for its irritant or poisonous effect on the human body."

Note, therefore, that gas can, in this instance, be a solid, a liquid or a gas.

(To be continued)

The Skipper

The amateur electrician should know these POLE-FINDING DEVICES

THOSE of our readers whose work is concerned with accumulator charging, primary batteries, dynamos, electroplating, etc. no doubt will often have found the need for quickly determining the polarity of a circuit when making connections, as it is especially important to see that the current passes the right way round, otherwise it may cause considerable damage to the work in hand. As, for instance, an accidental reversal of accumulator polarity when being recharged.

To guard against such occurrences there are various kinds of "Pole-finders" available, and although the experienced electrician may not often have need of them they are indispensable to the amateur.

Battery Polarity

Often the trained electrician will be able to determine without test which is the positive terminal of a primary battery from his knowledge of its construction. But those who handle batteries infrequently may not always remember




Fig. 1—Battery Elements and Poles



Fig. 2—Effect of current on Compass needle

that of the two "elements" in a battery it is the one which is acted upon most rapidly—that is, wastes away more quickly—that is the negative element.

Consequently, its outside terminal will always be the positive pole in the circuit. Fig. 1 will explain this apparent contradiction, and make clear the distinction between "elements" and "poles." Here there are two simple elements of Zinc (Zn.) and Carbon (C.), standing in a jar containing dilute sulphuric acid.

The Action

The zinc, being chemically acted upon by the acid, becomes electro-positive (+) to the carbon (—) in the solution. If the terminals of the two elements are connected together by a wire as shown by the dotted line, current would flow round the circuit in the direction shown by the arrows.

But if current goes in at one end of an element it must come out at the other. Hence the carbon is negative in the cell but its outer or terminal end is positive to the circuit as a whole, the

positive being the terminal at which current leaves the cell.

Nearly all primary batteries in commercial use have carbon for one of the elements and we know therefore that carbon not being chemically acted upon its outer terminal will always be positive.

Accumulator Polarity

With the ordinary lead-acid accumulators it is also easy to determine the polarity from inspection, provided the plates are visible and not sealed in. For the positive terminal will be that attached to the chocolate coloured set of plates, while the negative pole will be that connected to the grey set of plates.

In such cases as this, a casual glance is sufficient, but when the battery elements are sealed into an opaque case with only the terminals visible, and perhaps the original marking to distinguish the polarity has disappeared, it is then that some form of polarity finder becomes essential.

Most of these devices are quite simple, but they do not seem to be very familiar to most workers. Some are electro-magnetic, others are electro-chemical in action. The latter are the more sensitive where small current values or low potentials are concerned.

Magnetic Pole-finders

The first of these is the Compass Detector. Any ordinary compass with a freely pivoted needle about 1½ ins. long will serve the purpose, and if held directly underneath and parallel with a wire forming part of the electric circuit it will



Fig. 3—Deflection of Compass with current reversal.




Fig. 4—Liquid Pole-finder




Fig. 5—Polarity test with Lead strips.

deflect either to the right or the left when the circuit is closed, according to the direction of the current, thus indicating the polarity.

This is explained by reference to Fig. 2 and Fig. 3, and depends upon very simple first principles. When a wire is carrying current it becomes the seat of a magnetic field, the direction of which depends upon the direction in which current is flowing.

In Fig. 2, A represents a battery, B C a straight wire, and N S a magnetic compass needle, the

wire being placed parallel with the axis of the needle when the latter is at rest, and as close to it as possible.

If the battery circuit is now completed current will flow from its positive + terminal through B C in the direction of the arrow heads, setting up a magnetic field around it as indicated by the curved arrows.

This field naturally reacts upon the poles of the compass needle and according to the laws of the magnetic circuit that "Like Poles Repel" and "Unlike Poles Attract" the needle will be deflected left-handedly in the direction shown by its dotted outline. If the current in the wire is reversed in direction the needle will at once deflect in the opposite direction.

Fig. 3 shows these two conditions looking at the north end of the compass needle end-on. The figure on the left represents current passing along the wire away from the observer, and that on the right the conditions when coming towards him.

From the deflection of the needle, therefore, the direction of the current will be known and the consequent polarity of the battery terminals supplying it.

Galvanometers as Pole-finders

There are some forms of galvanometers and voltmeters used for general testing purposes in which the deflections are due to the current affecting a small internal permanent magnet.

Such instruments usually have their terminals plainly marked + and -. If, when connected to the circuit, of which the polarity is unknown, the needle deflects towards the right it is proof that the wire attached to the positive terminal comes from the positive of the battery. But if it deflects in the reverse direction that wire which is attached to the marked positive instrument terminal will be the one connected to the negative battery terminal.

Such instruments as these can therefore be used as Pole-finders, if the above fact is borne in mind.

Liquid Pole-finders

This class of pole-finder depends upon the electrolytic effect of current upon certain chemicals in solution.

One form consists of a glass tube, sealed at both ends with metal caps which form the terminals, containing water made slightly acid to render it a conductor of electricity.

The metal caps have pins which project into the solution, and when a direct current is passed through the tube the water is decomposed into its two constituent gases, hydrogen and oxygen. The oxygen collects in bubbles at the positive, and the hydrogen at the negative terminal.

Since there is twice the volume of hydrogen as of oxygen that terminal which is the more thickly covered with bubbles will be the negative (Fig. 4).

Another Method

Another simple liquid test for polarity is to immerse two small strips of clean sheet lead into a jar containing accumulator acid (Fig. 5). After

the current has been passing a short time one strip C will turn a chocolate colour, while the other strip G remains grey.

The chocolate strip is the one which has been attached to the positive pole.

Pole-finding Papers

It is not always convenient to deal with liquid pole-finders, and a very handy and portable type is that which takes the form of a chemically sensitised paper. Cut into strips and bound into small books this can be carried in the pocket and when required a strip can be torn out.

The strip requires to be moistened with clean water and the ends of the two wires to be tested laid upon it about a $\frac{1}{2}$ in. apart, when one pole will be permanently marked if the supply is direct current, but not if it is alternating.

One kind of test paper is the iodine-starch combination and in this the positive wire stains the paper purple where it touches. Another kind of test paper employs the chemical known as Phenolphthalein. This turns pink round the negative wire, but does not discolour at the positive.

How to Make

The iodine-starch pole-finding paper is easy to make up, the process being as follows. Dissolve half an ounce of saltpetre and half an ounce of potassium iodide in half a pint of warm water.

One ounce of starch is then made into a thick cream with a few drops of cold water, and half a pint of boiling water then poured on it stirring vigorously until it becomes "cooked." Add to this the ready-made solution of iodide while still warm, and stir well, the final product being very little thicker than water.

When cold, strips of white chemical filter paper $\frac{1}{2}$ in. wide are drawn through the mixture and hung on a line to dry. This is preferably done in the dark or the paper may discolour.

When quite dry, the paper strips may be cut into 2 in. lengths and pinned together in packets or "books" of 25 or 50 leaves, secured at one end by a brass paper fastener. This paper is non-poisonous and may be moistened by the tongue when required for use.

Neon Polarity Indicators

Finally there are one or two devices on the market, such as the "Voltascope" and the "Test-o-Lite," which consist of small neon gas-filled bulbs with two flexible electrodes or spike contacts in series with a very high resistance.

The primary use of such instruments is to trace faults in wiring, and to distinguish between the "live" and the "neutral" side of a circuit.

They also serve to show the difference between direct and alternating current, as either contact will cause the lamp to glow when applied to the terminal of an A.C. circuit, but only one if it is D.C.

The latter peculiarity makes it possible to use the instrument also as a polarity indicator when the circuit is supplied with direct current.

WHY NOT JOIN A MODEL AEROPLANE CLUB?

There are over 150 in this Country,
and **you** are sure to be living near
to at least one of them.

The names and addresses of all these
Clubs are published in the August
issue of the

AERO MODELLER
ON SALE JULY 20th

Price **6d.** for 56 pages all about
Model Aeroplanes.



Watching Smith, the old clock sighed, "It's rather
A shame to get into a lather.
Let me put you right
What you need is **FLUXITE**.
I learned that much from your grandfather!"

See that **FLUXITE** is always by you—in the house
—garage — workshop — wherever speedy soldering is
needed. Used for 30 years in Government Works and
by leading Engineers and Manufacturers.

OF ALL IRONMONGERS IN TINS
4d., 8d., 1/4 and 2/8

Ask to see the **FLUXITE SMALL SPACE SOLDERING SET**—compact
but substantial—complete with full instructions—7/6

Write for Free Book on the Art of "SOFT" SOLDERING and ask for Leaflet on
CASE HARDENING STEEL and TEMPERING TOOLS with **FLUXITE**.

TO CYCLISTS! Your wheels will NOT keep round and true
unless the spokes are tied with fine wire at the crossings AND
SOLDERED. This makes a much stronger wheel. It's simple
with—**FLUXITE**—but IMPORTANT.

THE FLUXITE GUN

is always ready to put "Fluxite"
on the soldering job instantly.
A little pressure places the
right quantity on the right spot
and one charging lasts for ages.

Price 1/6


ALL MECHANICS WILL HAVE

FLUXITE

IT SIMPLIFIES ALL SOLDERING


FLUXITE LIMITED, Dept. H., Dragon Works, Bermondsey St., S.E.

BALSA WOOD




"L" SECTION

$\frac{7}{16} \times \frac{1}{8}$ in. 4½d. length. 4/- doz.
 $\frac{1}{2} \times \frac{1}{8}$ in. 5d. length. 4/6 doz.



3ft. Lengths



"T" SECTION

$\frac{3}{16} \times \frac{3}{16}$ in. 6d. length. 5/6 doz.

This is sound quality Balsa Wood. It is amazingly easy
to work with knife or saw and is used by thousands of
model aeroplane builders. Use it, too, for model boat
hulls, toys, kiddies' building bricks, and a host of other
things. Balsa Wood is the wood without a substitute.

3ft. LENGTHS


Size	Each	Doz.
3in. \times $\frac{1}{8}$ in. ...	5d.	3/9
$\frac{1}{4}$ in. \times $\frac{1}{8}$ in. ...	1d.	10d.
2in. \times $\frac{1}{8}$ in. ...	3½d.	3/3
3in. \times $\frac{1}{8}$ in. ...	4½d.	4/3
6in. \times $\frac{1}{8}$ in. ...	8½d.	8/-
$\frac{1}{2}$ in. \times $\frac{1}{8}$ in. ...	1d.	11d.
$\frac{1}{2}$ in. \times $\frac{1}{4}$ in. ...	1½d.	1/4
6in. \times $\frac{1}{8}$ in. ...	11½d.	10/6
$\frac{3}{16}$ in. \times $\frac{3}{16}$ in. ...	1½d.	1/8
6in. \times $\frac{1}{8}$ in. ...	1/2	13/6

Size	Each	Doz.
$\frac{1}{4}$ in. \times $\frac{1}{8}$ in. ...	2d.	1/10
6in. \times $\frac{1}{8}$ in. ...	1/5	15/9
$\frac{1}{2}$ in. \times $\frac{1}{8}$ in. ...	2½d.	2/3
6in. \times $\frac{1}{8}$ in. ...	1/8	19/-
$\frac{1}{2}$ in. \times $\frac{1}{4}$ in. ...	3½d.	3/3
1½ in. \times $\frac{1}{8}$ in. ...	7½d.	7/-
6in. \times $\frac{1}{4}$ in. ...	1/11	22/-
$\frac{3}{16}$ in. \times $\frac{3}{16}$ in. ...	5½d.	5/3
1in. \times 1in. ...	7½d.	7/-
2in. \times 1in. ...	1/1½	13/-

Half the
Weight
of CORK

Postage.—There is a
minimum charge of
6d. to cover postage
and packing.

Hobbies Ltd.
Dereham



DOLL'S KITCHEN TABLE and CHAIR SET

Design No. 2233

See page 435

ONE $\frac{1}{8}$ IN..

INNER
 $\frac{3}{16}$ IN..

TABLE, END RAIL,
CUT TWO $\frac{3}{16}$ IN..

DRAWER
END,
CUT TWO
 $\frac{3}{16}$ IN..

CUT TO THIS LINE TO FORM DRAWER FRONT

TABLE, FRONT RAIL,
CUT ONE $\frac{3}{16}$ IN..

KNOB No. 80

FOR BACK RAIL, CUT ONE TO OUTLINE ONLY $\frac{3}{16}$ IN..

LEG

BACK RAIL

GRAIN
OF WOOD


END RAIL

END RAIL

FRONT RAIL

TOP OF TABLE, CUT ONE $\frac{3}{16}$ IN..

TABLE LEGS, CUT FOUR $\frac{1}{8}$ IN..



Tray Handles

Copper-bronze finish. Amazing value. Better quality from 1/8 pair. Write for list.

4 1/2 D. Pair
Post 2d.

Hobbies Ltd.
Dereham.

1 1/2 d. ft. Grooved Moulding

1/3 doz.
Post extra



In Hazel Pine with 1/4 in. (No. 48a) and 3/8 in. (No. 48b) groove. For cut-out calendars, etc.

HOBBIES LTD.
DEREHAM.

It must be good...

HOBBIES LEVER FRAME

This is the most popular fretwork hand frame in the world.

Prices


12in. 4/6
14in. 4/9
16in. 5/-
18in. 5/3
Postage 6d.

The top lever is a special feature, giving instantaneous tension to the sawblade. The lower wooden knob may be turned to raise or lower the bottom saw clamp, to give the precise tension required.

Hobbies Ltd. Dereham.

A Handle or Knob for every Job

In the Hobbies range you are almost certain to see just the Handle or Knob you want—at the price you want to pay.



Prices from 1d. to 1/-


See the 1938 Hand-book for full range.

Hobbies Ltd.,
Dereham,
Norfolk
and Branches.


Keep Your Tools where You can find them

TOOL CLIPS

2 1/2 d. each
2/3 dozen
Postage 4d.




Don't let your tools lie about just anywhere. Keep them neat and tidy in Hobbies Tool Racks and Clips. Cheap to buy they give lasting service.



TOOL RACK—13ins. long, 1/6 Post 4d. 18ins. long 2/- Post 6d.
HOBBIES LTD., DEREHAM. Branches and Agents in principal towns.

Are you all right for HINGES?




LIGHT BRASS HINGES

1/2 in. 1d. 1/2 in. 1d. 3/4 in. 1 1/2 d. 1 in. 2 1/2 d.
1 1/2 in. 3d. 2 1/2 in. 5d. per pair.

STOUT BRASS HINGES

1/2 in. 2 1/2 d. 1 in. 3d. 1 1/2 in. 3 1/2 d. 1 3/4 in. 4 1/2 d. 2 in. 5d.
2 1/2 in. 7d. per pair.



FANCY HINGE

No. 5379 1 1/2 in. wide.
Price 3d. per pair.


You need hinges for practically every woodwork job. Hinges for light fretwork articles or the heavier jobs of carpentry—ornamental hinges for decorative purposes—long hinges for cabinet lids. You can buy them all from Hobbies—and at right prices! All are in brass except where otherwise stated.

Add 1 1/2 d. extra when ordering by post. Screws are not included.



STRUT HINGE

No. 5364 1 1/2 in. wide.
Price 2d. each.



SCREEN HINGE

No. 5217. For 1 in. wood. Price 3 1/2 d. ea.
Fix with fine brass nails.



STRUT HINGE

No. 5369. 1 1/2 in. wide.
Price 2d. each.



FANCY HINGE

No. 5308 in two sizes.
1 1/2 in. 1 1/2 d. pair. 1 in. 2d. pair.
Fix with fine brass nails

HOBBIES Ltd., DEREHAM NORFOLK
and branches and agencies everywhere.

COMBINED GARDEN FRAME AND TOOL SHED

ALl keen gardeners need some kind of shed to hold their tools and implements. Even those already possessing one may well prefer to build something smaller and more compact for their tools and so be free to use the original shed for more extensive use. It is surprising how small a shelter will hold all the necessary tools for garden use.


The one illustrated, for instance, will hold garden roller and grass cutter, as well as spades, etc., and is provided with a compartment above, glass covered, for urging on seeds in the spring and storing plants through the winter.

Its construction is quite simple, any amateur carpenter can make it, and not expensive as it can be built in red deal.

To Suit Your Needs

First, as regards dimensions. These must vary according to what the shed is required to shelter. The height can be calculated by adding the distance A-B to that of the compartment above. Distance A-B can be anything reasonable, say 3ft., if only such tools as spades, etc. are to be housed. If, however, taller tools are to be stored, then the height should be increased accordingly.

Do not make it too much though or it will be inconvenient to reach the compartment above. In certain cases it will be better to increase the length of the shed so that tools, with long handles, can rest horizontally.



A useful and practical article for the small garden

As regards length, 3ft. or so will be enough, unless both roller and mower are to be accommodated as well as the tools already mentioned.

If in doubt, take the combined widths of roller and mower, add a foot and make the total the length of the shed. Simple enough.

The Floor

Make the floor first. This consists of in. thick T and G boards nailed to in. by 2in. battens. The boards can run lengthwise or back to front but, in either case, the battens must be short of the front edge of the floor to allow the bevelled step to fit beneath. Make the floor the full length and depth of the shed.

For the ends cut enough lengths of in. matchboarding to make up the height and nail to side battens of in. by 2in. stuff. The top is sloped off as seen in Fig. 2. Keep the battens in. short of the bottom edge. At A nail across a in. sq. fillet.

The two ends are now placed at either end of the floor, the battens actually resting on the floor, and are nailed to the edges of the floor boards. Turn over carefully and drive nails through the floor into the battens.

Back and Front

The back and front boards (matchboards again) are nailed across. The front boards only extend down to the batten A. Both back and front do not reach the full length but only to the end battens, therefore they are nailed to them.

This will leave the cut-ends of both side and end boards exposed so in the angle thus left nail a in. sq. fillet down. See detail of back corner, Fig. 3.

Fig. 1 shows a perspective view of the construction, the angle fillets mentioned being cut away one side to reveal the ends of the boards they cover at the front corners.

Ventilation Holes

On the inside, nail a fillet along back and front, level with fillets A at the ends. The boards, forming the bottom of the top compartment, are nailed to these fillets.

Four holes are bored through this bottom near each end to allow air to circulate from the cupboard space beneath. A division is useful. T. and G boards will do for this, nailed to the bottom of the compartment and the back and fixed between beads to the floor. Fig. 1 shows the whole at this stage and should make all clear.

Trim it each end to fit round the angle fillets at the corners, fit in place and secure with nails through the floor. It may be mentioned that the provision of this step is to facilitate running in the roller and mower. It can be omitted if those implements are not included.

Hinge the frame to the back of the shed with 1 in. by 2 in. steel butt hinges and let it overlap 1 in. all round.

Cover

Give the underside of the floor and battens a




Fig. 1—Perspective view of construction




Fig. 2—Ends of shed




Fig. 5—Jointing glazed lid

coat of creosote to protect against damp. Then apply a coat of paint to the shed, inside and out.

1 To glaze the lid, first press putty in the rebates, then lay the glass on top and press well down until the putty is only $\frac{1}{4}$ in. thick. Strip off superfluous putty squeezed out underneath and drive in a few sprigs over the glass to keep it firmly down. Now apply a finishing coat of paint all over.

In cold, frosty weather a small lamp should be kept lighted in the shed. This will warm the air sufficiently to ward off any danger to the plants arising from frosts.

Only a small lamp is needed, and it can be placed on the floor where no danger of fire is likely to occur.

Galleon Bases—(Continued from opposite page)


The angles inside the shallow box are strengthened by angle fillet.

For galleon bases, plain oak could hardly be beaten, although a light staining often softens them down. Painted bases seldom look so good as stained or varnished ones.

A base for a cabinet or an intricate casket would look well if ebonized and then varnished.

If the base described in Fig. 3 is to take, say, a waterline model of a liner, then the top surface should be painted to represent the sea, either oil or poster colour being used for this purpose.

BASES FOR MODEL GALLEONS



WE have from time to time been asked to supply designs for the bases of model galleons, ships engines, etc., and this week we are giving a few suggestions which may be worked up.

In Fig. 1 is shown a good all-round type of base, where, to form the lower member, four pieces of thick wood are mitred up and glued, and a second thicker piece put on the top to give solidity to the whole.

The upper member must be set out to allow a margin around the under base, and should be either chamfered around the top or rounded off.

Shape to the Hull

The actual rests for the galleon must, of course, be shaped to correspond with the hull of the boat. The true shape can be got by first cutting a cardboard templet and testing it against the model in hand. Then, transfer the outline to the wood and cut round with the fretsaw.

In Fig. 2 we show two plainer types of bases, but which require perhaps a little more work and fitting. The base at A consists of a long strip of wood, the length, of course, being set according to the length of the model.

At certain distances from each end of the strip, sinkings are cut with the tenon saw or fretsaw as shown in the diagram in the circle at the top. Into these recesses the uprights are glued after being shaped and fitted.

Recess Shapes

The shaped chamfers along the edges of the middle strip should be marked out for length and




Fig. 3—Base framing




Fig. 1—Framework and supports




Fig. 2—A simple shaped base

width and cut in with a sharp chisel. There is a recess made in each upright to fit that of the base so that a perfectly strong joint results.

In the larger circle in Fig. 2 (B), another base of similar design is shown. In this a flat strip is adapted with rounded ends, but no cut out recess, and the uprights are simply glued and screwed through to it.

The Simplest Form

This base is undoubtedly the simplest to make and requires but little wood. For models of a different type from galleons, we should suggest a base of perhaps a little heavier make, as no doubt the length and breadth will be much greater.

The detail of one angle of a built-up base is shown in Fig. 3. In this base there is a frame of flat deal wood halved together at the corners and glued and screwed together.

On this frame is glued and nailed a sheet of sound plywood cut exactly to the same size as the frame. Then on all four edges around this is fixed a moulding of such width that the deal frame and half the thickness of the plywood are covered.

A base of this construction is very strong, and sizes up to 24 or even 30 inches by about 6 to 8 inches in width, can be made this way.

For, say a 24 in. length of frame, the deal strips should be not less than 1½ ins. wide, and above this length the frame should be strengthened in the middle by a cross rail half-lapped into the long side rails.

Moulded Edging

Hobbies No. 303 Moulding which can be got in ¾ in., 1 in. and 1½ in. widths, make admirable edge finishings for a base, while for a heavier type of base, Hobbies No. 17 moulding would be very suitable. In using the mouldings, mark and cut the mitres accurately.

(Continued on opposite page)




Fig. 4—A box formation

Some of the jobs for you in THE GARDEN IN AUGUST

The Vegetable Plot

SPRING sown onions will need attention during August. In the warmer parts of the country and in early situations these should be lifted and laid out on shelves to dry before storing.

Where the onions are not yet ready for lifting the tops of the thick necked bulbs should be bent over for a week or two when they will be ready to be taken up for drying and storing.

It is a good time to make a sowing of winter onions. The bed should be well prepared and made firm as onions more than most plants need a really firm seed bed.

If a sowing of cabbage was made early last month the young plants will be ready for thinning, if the weather is dry they should also be well watered now and again.

Thin the Spinach

Another vegetable which will need carefully thinning at this time is July sown spinach. August is also the best month for cutting and drying many favourite herbs. When cut the herbs are hung to dry in a cool shady position.

Tomatoes will need looking after just now to get the best from them. Under ordinary weather conditions the fruit should be ripening steadily and it is a good plan during the first ten days of this month to stop the plants.

The best method of stopping is to cut off the top of the plant so further growth is prevented at the last fully open truss of flowers.

This truss will, if the weather proves kind, mature its fruit, but in a poor weather season this is not to be expected. After the plants have been stopped in this way they will send out a number of side shoots, as soon as they show themselves these side shoots should be removed or the plants will become choked up with foliage.

Finish planting winter greens and late broccoli as early in the month as possible. If the weather is dry when the planting is done well water the plants in to give them a good start, because they will never altogether overset a check at this stage.

Among the Flowers

IN the flower garden it is a big mistake to leave flowers to die on the plants unless the seed is wanted. Many plants will quickly leave off flowering if seed is allowed to begin to form, while if the flowers are cut as soon as they begin to fade or before this they will keep flowering freely for weeks. Also dead flowers on plants quickly make the garden look untidy.

The present is a good time to increase many varieties of pansies. This is best done by carefully separating from the parent plant the small rooted side pieces or tufts, avoiding hollow stemmed pieces for this purpose.

These small tufts will quickly begin growth again if planted in a cold frame, but if you have not one of these a very big proportion will grow and do quite well if carefully planted in the positions they are wanted to occupy out of doors. Especially if they receive attention with the watering can should the weather be dry while they are getting a hold in their new positions.


Dealing with Pentstemons

Those who have some fine plants of pentstemons of which they wish to take cuttings so that they have a supply for the following season will need a cold frame or glass in some form.

Strong side shoots of well seasoned wood should be broken from the parent plant and the lower leaves removed. A few pots will be needed and after making a horizontal cut just below the lowest joint the cuttings should be inserted round the sides of a pot. The pots are best filled with a light sandy loam.

If only very small pots are at hand one cutting may be inserted in each pot, but usually the cuttings will root more quickly if placed at the side rather than in the middle of the pots.

If there is only one cutting to a small pot it will be easier to move the plants to larger pots later without checking the growth. The cuttings



should be well watered and placed in the frame which is closed down and shaded in bright sunshine.

Later Handling

When the cuttings are rooted the lights should be lifted in mild weather but closed and protected during frost. About March the plants should be placed in larger pots and about the second week in May they may be planted where they are to flower.

Plants grown in this way will flower before those raised from seed or by division of the roots.



A cutting of Pentstemon and how to insert round a pot

Hollyhocks may be increased by cuttings during this month as may also fuchsias and cuttings of hardy shrubs may be taken and inserted for rooting now.

Fruit

As soon as raspberry canes have finished fruiting the old canes are best removed. Late strawberries will be well over by now and if not begun earlier a start ought to be made with getting the beds clean and in good order at once.

The best way to get rid of the rubbish is to burn it, the old leaves of the strawberry plants should be cut off and burned at the same time.

Testing for Ripeness

A few early varieties of apples and pears are ready at this time, but if the fruit is wanted for eating or for storing it is a mistake to gather it before it is really fit.

The best method of testing fruit to find out whether or not it is ready to gather is to lift it on the palm of the hand while still on the tree.

If a few fruits are tested in this way and four out of six part from the tree without being gripped or twisted it may be taken for granted that the apples or pears on that tree are ready and may be gathered for storing or eating.

Cooking apples are sometimes gathered before they are ripe, for use at once, but it is only a waste of the fruit to gather for storing before it is fully fit.

Try the novelty of having a HIKE AT NIGHT

FEW people know of the pleasure and excitement of hiking at night, but for experienced hikers there are few expeditions giving more fun. For a first hike choose a short summer night.

Even at mid-summer nights are often very cold and it is a good idea to have a hot drink before leaving, whether hiking from home or from camp.

A warm pullover is a distinct asset and it takes up very little room in a rucksack. Do not attempt a long hike to begin with. The secret of not tiring oneself out is to go easy, and keep going. Walk slowly enough to give the slowest member of the party a chance to keep up, but don't dawdle!

Keep Together

The party should endeavour to keep together for even familiar ground is confusing in the dark. Marshes, over-grown ditches and undergrowth hold dangers for the unwary, and for this reason it is wise to use routes well-known to yourselves for the first few hikes.

Trees and other objects cast weird shadows in some lights and even the most confident stalwart may find he possesses nerves!

A rucksack is very much more convenient than a haversack for carrying kit even on a very short hike. It is put on your back and it stays there wherever you may happen to scramble, whereas a haversack slips round and gets in the way.

On a night hike you will need to carry an extra pair of stockings (in case you step in that bog!), a warm pullover, a map and compass if you think you will need them and, of course, some food.

Midnight Cooking

You may be tempted to take only chocolate and sandwiches with you, but you will probably find, that a hot meal at one o'clock in the morning is most welcome. Besides, cooking your own meal adds to the fun!

In the very early hours of the morning vitality is at a very low ebb and spirits are inclined to flag. The excitement of lighting a fire and cooking a meal in the open and in the middle of the night helps to add a dash of adventure and keeps up the enjoyment of the hike.

Suitable Food

There is no need to name here various hike dishes, but choose those which are simple and do not need much cooking, at least, for first attempts at night hiking. Fruit and chocolate should be included on your menu.

The coldest part of a summer night is between two and half-past two, just before dawn begins to break. Try to be on the road again by then.

Saturday night is possibly the most convenient time for a night hike as there is a better possibility of a good rest on the following day.

Here are some practical hints on PREPARING WOOD SURFACES

A GREAT many young woodworkers often spoil otherwise splendid pieces of work through not knowing how to prepare the wood properly for its finish. Just planing and glasspapering is not enough—unless the article is some rough affair of no great importance.

But, taking things that are important, such as furniture, the preparation demands all the skill one can muster. Even if the wood is cheap, soft stuff like deal, it must be made beautifully smooth and free from waves and tears.

These, though some sometimes invisible to the eye, always show up pretty badly under the coating of paint, enamel, varnish or polish, and in consequence, marks one down as a very careless worker.

Preparing Soft Wood

Fortunately, it is easy to learn and improve upon one's capabilities, providing you have the determination and the correct implements. For timber like pine and deal, a wooden smoothing plane and several grades of glasspaper, together with the cork block (or one made from wood faced with lino) would suffice.

Now, if you look closely at machine-planed timber and move your finger tips lightly over the surface, you will find minute waves or hollows running across. This is due to the rotor-cutting "irons" of the planing machine.

Though planed, therefore, the wood is never quite ready for use. Having selected the best (face) sides of the various parts of the article you are making, mark such with an X or by a looping curve running to the edge that has been straightened and squared.

The smoothing plane must be keenly sharpened and set finely. The cutting edge of the iron, incidentally, must be slightly—very slightly—concave. If too concave or straight, it will cause a series of hollows and streaks upon which glasspaper will have little effect.

When working with deal and other soft wood, the cover of the cutting iron should be adjusted to about $1/16$ in. from the cutting edge.

If the grain is coarse and dotted with "live" and "dead" knots, the adjustment must be as fine as possible—not too fine or the shaving will crinkle up and gather tightly at the mouth of the plane. The whole iron should be also wedged in to project the minimum. That is the secret of good smooth planing.

Mind the "Flat" Grain

Before planing a board, always look at its edges to see how the "flat" or surface grain is running. If straight with the thickness of the board you can plane it right or left, but if, for instance, it is *leaning* towards the right, it must be planed in that direction, while the other side is planed the oppo-

site way. This saves "digging" up the grain and causing yourself unnecessary labour and bother.

When planing, do it methodically and conscientiously. You have, at the outset, only to remove the wavy marks set up by the planing machine. Roughness around knots should be given special care.

You should try to remove one complete shaving from the board—that is, from head to foot. If very long, shave from the foot to the centre (raise the plane up here) and carry on to the head end. Always shave from left to right of the board, not up the middle or here and there.

This means general evenness and coarse, medium and fine glasspaper will do the rest. Some workers rub the coarse paper across the grain, then with the grain, the medium and fine grades being rubbed with the grain only.

Use of a Scraper

With hardwood like oak and mahogany, a good wooden or iron smoothing plane, plus a scraper is essential. Unlike that of deal, the cover of the iron must always be set fine, particularly with the mahogany which has usually "cross" grain patches.

By having the plane cutter razor keen and adjusted the minimum, you can abolish all care about the grain direction. A really well set plane will shave just as easy against the grain as with it.

Naturally, however, there are bound to be slight marks and roughness, but such can be corrected with the scraper. This, as you might know, is an oblong piece of sheet steel about 5 ins. by 3 ins. by $1/16$ in. thick.


The longer edges are filed square and flat and dressed on an oilstone. The edges are turned over with the back of a gouge or a piece of smooth steel rod so the "burr" is sharp and cuts into wood similar to the keen edge of a broken piece of glass.

How a Scraper is Held

The scraper is held firmly on the wood before you with both hands, the thumbs being pressed behind it close to the bottom or cutting edge. The pressure of the thumbs keeps the edge steady on the timber as you push the scraper forward to bring forth tiny, extremely fine shavings. Hold the scraper at an almost upright angle so the "burr" eats into the wood.

After scraping, use the three grades of glasspaper to make the surface even smoother. A fourth grade is sometimes used, this being No. O or No. OO.

When scraped and glasspapered, some cabinet-makers "lift" the grain and possible dents by damping the wood surface slightly with a wet rag, then scrape and glasspaper it again when the wood is dry.



SPORTS SILHOUETTE STATUES IN WOOD

SOMETHING new and pleasing for you.




Novel little stands just $3\frac{1}{2}$ ins. high with realistic figures of sports in outline. Several ways of doing it too, but all with a pleasing result. The circular base is cut in $\frac{3}{16}$ in. wood and the oval upright in $\frac{1}{2}$ in. wood.

The sports figures can be cut from thin wood ($\frac{1}{16}$ in.) the ivory (cream) or xylonite (polished black) composition, sheet bakelite or similar compositions.

The background should contrast with the figure—polished black ground for ivory cut-out, etc. Ebony colour polish very suitable.

Line in the figure more, if you can draw, or leave in plain outline. Glue the overlay part on securely and in proper position. If a polished surface, scratch it to make the glue hold.

If you wish carve out the base to make stud tray.



MISCELLANEOUS ADVERTISEMENTS

The advertisements are inserted at the rate of 2d. per word prepaid. Name and address are counted, but initials or groups, such as E.P.S. or L11/6 are accepted as one word. Postal Order and Stamps must accompany the order. They will be inserted in the earliest issue. To sell anything except fretwork goods or those shown in Hobbies Handbook. Orders can be sent either to Hobbies Weekly, Advertisement Dept. 30/32 Ludgate Hill, London, E.C.4, or Dereham, Norfolk.

100 STAMPS all different, sent genuine applicants for approvals. Postage 2d.—**Errington Macquire** (O), 51 Atkins Road, London, S.W.12.

GLUE. Hobbies glue is as good as 25 years' experience can make it. Sticks wood, china, leather, etc. In tubes 6d. and 2d.—**Hobbies Ltd., Dereham.**

LONELY? Then write Secy., U.C.C., 16BB. Cambridge St., London, S.W.1. Genuine. Estab'd. 1905.

FRAME YOUR OWN PICTURES! We supply mitre block, cramps, mouldings, etc. Easy, fascinating work. Profitable, too!—**Hobbies Ltd., Dereham.**

50 STAMPS FREE. Approvals 2d. stamp.—**Paul,** 43 Bramley Road, London, W.10.

WHY NOT TREAT YOURSELF to a fretmachine? It will double your output in half the time. Prices from 35/- cash or easy payments.—**Hobbies Ltd., Dereham.**

1-HORSE-POWER and fractional horse-power. Aero, 2 Petrol, Motor Castings. All sizes in stock. Interesting catalogue 3d.—**Butler, Aero Works, Wade Street, Littleover, Derby.**

THE WORLD'S MOST POPULAR FRETWORK SET—**Hobbies A1,** price 12/6; post 9d. Other sets from 1/6 to 25/-. Send for list.—**Hobbies Ltd., Dereham.**

FREE! Crete Revolution, Hayti Commemorative, Indo-China and Bolivia Pictorial, to applicants for bargain approvals. Postage.—**Norris, Chilton, Aylesbury, Bucks.**

ASTRONOMICAL TELESCOPE OUTFITS 5/6!! For assembling 32ins. instrument. Comprising 1 1/2 in. aperture objective with Brass Cell. Superior Eyepieces with Tubes. One day, two celestial, magnification 12, 35, 50 diameters (latter equivalent 2,500x area). In compartment Box with illustrated instructions.—**Below.**

MIDGET ELECTRIC AERO MOTORS 8/6!! Masterpiece in Miniature. Weight only 50 grammes!! 1 1/4 1/2 volts. 2,000/4,000 R.P.M. Royal Blue Tubular Case. Diameter 24mm., length 30mm. Complete in Box with 3 midget 3oz. cells (operates from one or more) with instructions. Also suitable for Speed Boats. Enormous experimental field.—**Below.**

LARGE STUDENTS MICROSCOPES 7/9!! Compound Lenses. Magnification 200 diameters (equivalent 40,000 x area) Rack Pinion. Inclined Claw-Foot Stand with Mirror.—**Below.**

MIDGET TELESCOPES 1/3!! Open fountain size. 10 mile range. Triple brass sections. Bound in real hide. 2 for 2/.—**Below.**

4-VOLT AC/DC ELECTRIC MOTORS 1/-!! 6,000 r.p.m. Complete kit of parts easily assembled, with illustrated instructions in box. 2 for 1/9.—**Below.**

ABOVE POST FREE. C.W.O., C.O.D. 1/- extra. Postage extra. **J. K. M. Holmes,** Scientific Instrument Dealer, Dept. H2, "Vizcaya," Wolveleigh, Gosforth, Newcastle-on-Tyne.

POLISH OUTFIT 2/3; post 6d. Comprises three kinds of stain crystals, woodfiller, cotton-wool rubber, bottle of Hobbies "Lightning" polish, glasspaper and instructions.—**Hobbies Ltd., Dereham.**



Realistic Traffic Lights. 7 1/2 ins. high, with 3-lamp switch. With battery.

2/11
Postage 4d.



Petrol Pumps of Esso or Shell. Lights lamp when pumped 6 ins. high. Complete with battery inside.

2/11
Postage 3d.



Realistic Light-house on rocks. Lamp which lights. Complete with battery inside.


2/11
Post 4d.

Models..

BOYS..... Here's a chance to buy some fine electric working models. If you are making a Doll's House why not get the set of bathroom fittings in polished aluminium.

BATHROOM FITTINGS

Bath (4 1/2 ins. long) 1/3; Washbasin (2 1/2 ins. high) 1/6; Stool (1 1/2 ins. high) 9d.; Towel Arier 6d. and 1/-; Mat 6d.; Fireside Set, 1/6. Post 2d. extra.




SEARCH-LIGHT

With Powerful lens. Stands 4 1/2 ins. high. Well finished and fitted with battery. **3/6**
Postage 6d.



Obtainable from **Hobbies Ltd., Dereham, Norfolk,** or branches in **London, Glasgow, Manchester, Birmingham, Leeds, Sheffield, Southampton and Hull.**



French Celebrities

FRANCE has issued a very large number of stamps lately which have had the portraits of various men. In some cases, these stamps have had the portrait of men of world-wide fame, and when this has been the case then it has been easy to write up the lives of these celebrities in such a



Pierre Loti

way that all who read will appreciate why they should appear on the stamps which go through the post.

The difficulty is now that there are a few which can hardly be termed world-famous, but as philatelists we are very liable to be asked who is this man who is portrayed on this stamp. And to answer that you do not know anything about him is rather weak.

So this time we have to consider a few names and faces which have appeared, and about which we may expect to be questioned.

The first illustration is of the charity stamp value, 50c. plus 20c. It shows a portrait of Pierre Loti, or at least, that is the name given on the stamp. Actually, it is only the pen name of the French Novelist Louis Marie Julien Viaud.

He was born at Rochefort, on Jan. 14th, 1850. In 1867 he entered the French Navy, and became a captain in 1906. In 1879 he produced his first tale, "Aziyade." It is a story of the Bosphorus, and it is the Bosphorus forming the view which appears on the left of the stamp.

In 1880 came "Rarahu," which was reprinted in 1882 as "Le Mariage de Loti," the story of an Englishman and a Tahitian girl. This won for him instant popularity, but curiously enough

his books are lacking in much that goes to make up a plot.

In 1886 he wrote "Le Pecheur d'Islande." In 1923 he died on June 10th, having been a member of the French Academy since 1891.

Another Frenchman who has been similarly honoured is Leon Gambetta. He was born at Cahors on April 2nd, 1838, and he studied law at Paris. Turning to politics, he was elected to the Chamber of Deputies in 1869.

After the Emperor's surrender in 1870 at Sedan, he became Minister of the Interior and of War, in the Government of National Defence. He escaped from Paris in a balloon, and went to Tours where he did a great deal to arouse the French against the Germans.

He is regarded as one of the founders of the Republic, because through newspaper efforts he did so much to strengthen the constitution.

He was elected President of the Chamber in 1879, and was Premier from 1881 to 1882. An accidental wound from a pistol brought



Leon Gambetta

Jean Charcot

about his death in 1882; the last day of that year actually.

The third illustration shows another Frenchman who has earned the right to have his portrait on the postage stamps of his country. It is Jean Charcot, who captained the "Porquoi Pas" which was lost with all hands off Greenland last year.

Below the name is seen the inscription 'Société des Œuvres de mer' and this informs us that the stamp is issued in aid of a

charity for merchant seamen. The premium of 35c. goes to this, the postal value being 65c.

Great Men on Stamps

IT is some little time since we considered some of the lives of the great men whose portraits appear on postage stamps. A year ago, July 20th, 1937, Guglielmo Marconi passed away.

Italy has honoured this great man with an issue of three stamps, 20, 50 and 1 lire 25 centesimi. The design is a very plain one, but the man portrayed was surely one of the most important men of the world.

He was born at Bologna on April 25th, 1874, and his mother was Irish. Marconi took out an English patent and made his first demonstrations from the G.P.O. St. Martins-le-Grand, London, in 1896. The next year he was invited by the Italian Government to superintend the erection of a land station which was able to communicate with Italian battle-ships. A company was also formed in England to take over his patents except in Italy.

In 1900 Marconi built a long-distance station in Cornwall which successfully sent messages to Newfoundland. He served in the Italian Army and Navy during the Great War.

He began experiments with the short waves which led to the 'beam' system of long distance and directed wireless transmission. He owned a yacht called the 'Electra' and many of his experiments have been made from this.

In 1909 he was awarded the Nobel prize for Physics, and he was made a Senator in 1915 and a Marquess in 1929. Through his death a year ago science lost a splendid research student.



Count Marconi

Big bargains in Stamps in our Miscellaneous Adverts.

An Expert Designed It...

3ft. 10in.
Wing Span
14in. "Prop"



Hobbies Ltd., Dereham,
Norfolk and Branches

You will be thrilled at the wonderful performance of this splendid model. An expert designed it. From tip to tip of its 3ft. 10ins. wing span it reflects the touch of a master hand. Remember, this is no midget.....but a model you will be proud to fly anywhere. The kit of parts costs only 19/6 and is really cheap at the price. Start building it NOW!

Build it from this Kit


The Kit includes 14in. Aircscrew, balsa, spruce, birch, gears, piano wire, 1½yds. Jap Silk "Durofix," 20yds. strip rubber, etc. and costs only 19/6; postage 6d. The design chart (No. 2121) and instructions cost a further 6d.

A Flying Model


LOW-WING MONOPLANE

TRANSFERS

Transfers cost little but add lots to the appearance of a job. A tray, cabinet door, or panel is often beautified by the addition of a suitable transfer. They are easily applied with Hobbies Special Transfer Fixer which costs only 6d. and 9d. per bottle. Postage is extra to all prices.



No. 5195. 1½ in.
× 1 in. Price ½d.



No. 5270. 4½ in. ×
3½ in. Price 2d.




No. 5617. 3 in.
high. Price 1d.



No. 5608. 6 in.
high. Price 3d.
No. 5609. 3 in.
high. Price 1½d.

No. 5349.
1 in. × ½ in.
No. 5350.
1½ in. × 1 in.
½d. each.



FREE LISTS

A special illustrated list of the full range of transfers is obtainable free from any Hobbies Branch or by post from Hobbies Ltd., Dereham, Norfolk.

TRANSFER BANDINGS

These strips are 23ins. long and are illustrated about one-half actual width.

No. 5230.
Black and Box.
Price 2d.



No. 5231.
Black and Box.
Price 2d.



No. 5232.
Black and Box.
Price 2d.




No. 5234.
Black and Box.
Price 1½d.



No. 5235.
Black and Box.
Price 1½d.



No. 5238.
Box only, 1d.



No. 5239.
Mother-of-Pearl
and Rosewood.
Price 3d.



No. 5240.
Box only, 1d.



No. 5241.
Black and Box.
Price 1½d.



No. 5242.
Black and Box.
Price 1½d.



No. 5243.
Satinwood.
Price 2d.



HOBBIES

BRANCHES AND AGENCIES. LTD.

Below are the addresses where Hobbies goods can be purchased. In addition, all leading stores and ironmongers stock or can obtain your requirements in fretwork and woodwork, designs, wood, turned legs, moulding, polish, etc.

HOBBIES OWN BRANCHES—

LONDON — 16 NEW OXFORD STREET, W.C.1.
LONDON — 147 BISHOPSGATE, E.C.
LONDON — 83 NEWINGTON BUTTS, S.E.11.
GLASGOW — 326 ARGYLE STREET.
MANCHESTER — 10 PICCADILLY.
BIRMINGHAM — 9a HIGH STREET.
SHEFFIELD — 4 ST. PAUL'S PARADE.
LEEDS — 10 QUEEN VICTORIA STREET.
SOUTHAMPTON — 25 BERNARD STREET.
HULL — 13 PROSPECT STREET.
CANADA
54 WELLINGTON STREET WEST, TORONTO.

HOBBIES AGENCIES—

Aberdeen.—Jas. Mutch, Ltd., 47 Broad Street; Blackburn.—Mr. H. Mercer, 68 Darwen Street; Bradford.—Messrs. T. Underwood & Co., 17 Lower Godwin Street; Brighton.—J. B. Bennett & Co., North Road; Cambridge.—Mr. H. S. Driver, 28 Hills Road; Canterbury.—Mr. T. D. Goodman, 33 Burgate Street and 16 St. George's Street; Cardiff.—John Hall (Tools) Ltd., 22 and 24 Morgan Arcade; Croydon.—L. H. Turtle, Ltd., 6 Crown Hill; Dover.—Mr. E. F. Bockham, Queen's Gardens; Dublin.—Mr. J. J. McQuillan, 36 Capel Street; Dundee.—Phins Ltd., 29 Nethergate; Folkestone.—Mr. W. Allsorth, 16 and 18 Guildhall Street; Hastings.—Mr. W. H. Mozley, 4 York Buildings; Leicester.—Mr. Frank Berry, 3 Loseby Lane; Liverpool.—Mr. C. Lucas, 17 Houghton Street; London.—Messrs. H. Osman, 166 Aldersgate Street, E.C.; Newport, Mon.—John Hall (Tools) Ltd., 81 High Street; Reading.—Mr. W. J. Sargent, 44 West Street; Swansea.—John Hall (Tools) Ltd., 8 Gower Street; York.—Messrs. J. H. Shouksmith & Sons, 132 Micklegate.

HEAD OFFICE AND WORKS:

DEREHAM, NORFOLK

GENERAL NOTICES.

EDITORIAL.

All Editorial matter should be sent to The Editor, Hobbies Weekly, Dereham, Norfolk. If enclosed with orders or other matter for Hobbies Ltd., it should be written on a separate sheet of paper. Any matter requiring an answer must have a stamped addressed envelope enclosed.

DESIGN SHEETS.

The presentation Design Sheet is given only with current copies of Hobbies Weekly, and not with back numbers. The designs, however, can be obtained separately, from Hobbies Ltd., price 4½d., post free, or 10d. in the case of double size sheets.

ADVERTISEMENTS.

All orders and letters respecting advertisements should be addressed either to the Advertisement Manager, Hobbies Weekly, Dereham, Norfolk, or to 30/32, Ludgate Hill, London, E.C.4.

INDEXES AND BINDING CASES.

An Index for any volume is obtainable for 4½d. post free, and Binding Cases to take a complete set of 26 issues (making the volume) are supplied for 1/6, or sent post free for 1/8. The Cases are in red linen with gold blocked name on the front. The Azabook Binder, to hold 24 copies which you can fix in yourself is 3/3 (3/6 post free) including two dozen fastening staples.

BACK COPIES.

Back copies are obtainable from the Editorial address given above or from the Publisher, price 2d. a copy, plus postage.

CONTRIBUTIONS.

The Editor is always pleased to consider suitable articles for these pages, which, if accepted, will be paid for at the usual rates. While every effort will be made to return unsuitable contributions (if stamps for that purpose are sent with them), the Editor does not accept any responsibility for their loss.

SUBSCRIPTION.

Hobbies will be forwarded by post to any part of the world at the following prepaid rates. Twelve months 13/-, six months 6/6, three months, 3/3. Registered for transmission by Canadian Magazine Post


OVERSEAS POSTAGE RATES

For the sake of those readers living abroad who order their goods from England, we give below the postal charges on parcels from some of the principal countries. If the weight of the goods are known, the amount shown in the proper column should be added to the remittance when the goods are ordered. A special leaflet giving particulars of postage in other countries is obtainable on request to the Export Dept., Hobbies Ltd., Dereham, Norfolk, England.

	Not over					Not over				
	2 lbs.	3 lbs.	7 lbs.	11 lbs.	22 lbs.	2 lbs.	3 lbs.	7 lbs.	11 lbs.	22 lbs.
Australia 1/4 per lb. and 6d. per lb. after up to 11 lbs.										
Barbados ..	1/6	1/6	3/-	4/3	6/9	2/3	2/3	4/-	6/3	9/3
British Guiana ..	1/9	1/9	3/-	4/3	7/9	2/6	2/6	3/6	5/-	7/6
Ceylon ..	2/-	2/-	3/9	5/3	7/9	2/3	2/3	3/6	4/6	8/-
Dutch East Indies ..	4/-	5/6	5/6	6/3	10/3	2/3	4/-	4/-	5/3	—
Egypt ..	2/-	2/-	3/6	4/6	7/3	1/9	1/9	3/-	4/3	6/6
France ..	1/6	2/3	2/3	2/9	4/3	1/9	1/9	3/3	5/-	7/9
Gibraltar ..	1/6	1/6	2/9	3/9	6/3	2/-	2/-	3/9	5/6	8/-
Gold Coast ..	2/6	2/6	3/6	4/9	7/-	2/6	2/6	3/6	4/9	7/-
India ..	2/-	2/-	3/9	5/3	8/3	9d. per lb.—11 lbs. only.				
Iraq ..	3/3	3/3	4/9	6/-	11/6*	1/4 per lb.—11 lbs. only.				
Jamaica ..	1/6	1/6	3/-	4/-	6/6	1/8 per lb.—11 lbs. only.				
Kenya and Uganda	2/9	2/9	4/6	6/3	10/3	2/-	2/-	3/3	4/6	7/9
Malay States ..	2/-	2/-	3/3	4/6	7/9	2/9	2/9	4/6	6/3	10/3
Malta ..	1/6	1/6	2/9	3/3	6/-	1/9	1/9	3/3	4/9	7/-
Newfoundland ..	2/-	2/-	3/6	4/9	8/-	2/-	2/-	3/9	5/9	9/9
						2/3	2/3	3/9	5/6	9/6

Irish Free State, 2 lbs. 6d., 5 lbs. 9d., 8 lbs., 1/-, 11 lbs. 1/3 *Up to 20 lbs. only.

A USEFUL SMALL HAMMER



With comfortable wooden handle and strong well-shaped head. 9½ins. long.

5d. Post 2d.

Obtainable from Hobbies Ltd., Dereham, Norfolk, or any branch or Agency.

REPLY COUPON

One of these small Coupons and a stamp for 1½d. must be attached to your letter to the Editor, if you are enquiring about anything which demands an answer. Cut the Coupon out and put it in with your letter which should be addressed to The Editor, Hobbies Weekly, Dereham, Norfolk.

An Old Favourite In a New Form . . .



*. . . at a Record
Low Price!*

Hitherto, you had to pay 90/- for a Fretmachine fitted with a Drilling Attachment. Now—with the introduction of this new A1—you can buy the world's most popular fretmachine, with a treadle drilling attachment, for only 70/-.

A Time Saver!

If you have never before used a Fretmachine fitted with a treadle drilling attachment you have a new experience . . . a new delight in store. It works so smoothly that you are hardly conscious of any extra effort when treadling. It drills all the holes for interior fret-cutting in a fraction of the time spent with the ordinary hand drill. When the attachment is not required the belt is easily thrown off and the machine used in the usual way.

Buy from any Hobbies Branch or Agent,
or direct from Hobbies Limited, Dereham,
Norfolk.



70/-

Carriage Forward

HOBBIES A1 MACHINE With Drill

Or supplied on easy payments of 7/- down and 28 payments of 2/6.